



Grosime pachet	Pachet sticla	Transmisie termica Ug W/(m²K)	Factor solar g	Transmisia luminoasa TL (%)	Reflexia externa RLe (%)	Reducia acustica Rw(C;Ctr) (dB)	Confort pe timp de iarna	Confort pe timp de vara	Confort pe timpul zilei	Confort acustic	Siguranta	Securitate	Economii de energie
60 mm	44.2SI Low-E / Dt20 / F6 / Dt18 / 44.2SI Low-E	0,5	0,49	71	14	47(-2;-8)	✓+		✓	✓+	✓	✓	✓+
60 mm	44.2 SUN / Dt20 / F6 / Dt18 / 44.2SI Low-E	0,5	0,33	61	15	46(-3;-7)	✓+	✓+		✓+	✓	✓	✓+
52 mm	44.2 SUN / Dt18 / F4 / Dt16 / 33.1 Low-E	0,5	0,33	64	16	40(-2;-6)	✓+	✓+	✓	✓+	✓	✓	✓+
52 mm	44.2 SUN / Dt18 / F4 / Dt18 / Low-E 4	0,5	0,33	64	16	38(-2;-7)	✓+	✓+	✓	✓+	✓	✓	✓+
52 mm	33.1 SUN / Dt18 / F4 / Dt18 / 33.1 Low-E	0,5	0,33	63	15	37(-2;-6)	✓+	✓+		✓	✓		✓+
52 mm	33.1 Low-E / Dt18 / F4 / Dt18 / 33.1 Low-E	0,5	0,5	72	14	37(-2;-6)	✓+		✓	✓	✓		✓+
52 mm	SUN6 / Dt18 / F4 / Dt18 / 33.1 Low-E	0,5	0,35	64	16	36(-3;-8)	✓+	✓+	✓	✓	✓		✓+
52 mm	SUN6 / Dt20 / F4 / Dt18 / Low-E 4	0,5	0,35	65	16	35(-2;-6)	✓+	✓+	✓	✓			✓+
48 mm	44.2SI Low-E / Dt16 / F4 / Dt14 / 33.1 Low-E	0,6	0,50	72	14	42(-3;-8)	✓+		✓	✓+	✓	✓	✓+
48 mm	44.2 SUN / Dt16 / F4 / Dt14 / 33.1 Low-E	0,6	0,33	64	16	39(-2;-5)	✓+	✓+	✓	✓+	✓	✓	✓+
48 mm	33.1 Low-E / Dt16 / F4 / Dt16 / 33.1 Low-E	0,6	0,51	73	14	35(-3;-8)	✓+		✓	✓	✓		✓+
48 mm	SUN6 / Dt18 / F4 / Dt16 / Low-E 4	0,5	0,35	65	16	35(-2;-6)	✓+	✓+	✓	✓			✓+
48 mm	33.2SI Low-E / Dt16 / F4 / Dt16 / 33.2SI Low-E	0,6	0,49	72	14	42(-1;-7)	✓+		✓	✓+	✓		✓+
48 mm	33.1 SUN / Dt18 / F4 / Dt16 / Low-E 4	0,5	0,34	65	16	35(-2;-6)	✓+	✓+	✓	✓	✓		✓+
48 mm	33.1 SUN / Dt16 / F4 / Dt16 / 33.1 Low-E	0,5	0,33	63	15	39(-2;-7)	✓+	✓+		✓+	✓		✓+
48 mm	Low-E 4 / Dt18 / F4 / Dt16 / 33.1 Low-E	0,5	0,54	74	14	37(-2;-6)	✓+		✓	✓	✓		✓+
48 mm	Low-E 4 / Dt18 / F4 / Dt18 / Low-E 4	0,5	0,54	74	14	30(-2;-6)	✓+		✓				✓+
36 mm	44.2 SUN / Dt20 / 44.2	1,0	0,35	69	13	40(-2;-6)	✓	✓+	✓	✓+	✓	✓	✓
36 mm	44.2 / Dt20 / 44.2 Low-E	1,1	0,59	79	11	40(-2;-6)	✓		✓	✓+	✓	✓	✓
32 mm	44.2SI Low-E / Dt18 / 33.1	1,1	0,57	80	11	41(-2;-7)	✓		✓	✓+	✓	✓	✓
32 mm	44.2 SUN / Dt18 / 33.1	1,0	0,36	70	14	38(-2;-5)	✓	✓	✓	✓+	✓	✓	✓
32 mm	33.1 / Dt20 / 33.1 Low-E	1,1	0,6	80	11	34(-2;-6)	✓		✓		✓		✓
32 mm	33.1 SUN / Dt20 / 33.1	1,1	0,36	69	13	34(-2;-6)	✓	✓	✓		✓		✓
28 mm	33.2 / Dt16 / 33.2SI Low-E	1,1	0,60	80	11	40(-1;-6)	✓		✓	✓+	✓		✓
28 mm	33.1 SUN / Dt16 / 33.1	1,0	0,36	69	13	35(-1;-5)	✓	✓	✓	✓	✓		✓
28 mm	SUN 4 / Dt18 / 33.1	1,1	0,37	70	13	36(-2;-6)	✓	✓	✓	✓	✓		✓
28 mm	F4 / Dt18 / 33.1 Low-E	1,1	0,65	81	11	34(-1;-5)	✓		✓		✓		✓
28 mm	F4 / Dt20 / Low-E	1,1	0,65	82	11	30(-2;-5)	✓		✓				✓